

The background image shows two construction workers in a room with a newly laid, highly reflective floor screed. One worker in the foreground is wearing a red hard hat and a high-visibility yellow vest, looking down at the floor. Another worker in the background is also in similar gear, including green rubber boots, and is using a long-handled tool to work on the floor. The floor is a light grey color and shows clear reflections of the workers and the room's walls.

HydriFlo

Alpha Hemihydrate Self-levelling Floor Screed

- Factory produced to EN 13813
- Perfect level floors
- Reduced screed thickness
- Improved U-values
- Maximises UFH performance



Call Turley Bros on (028) 3026 6421 www.turleybros.com

HydriFlo is a pump applied self-levelling Alpha Hemihydrate floor screed and is suitable for:

- **Underfloor Heating**
- **Commercial floors**
- **Residential floors**

What is it?

HydriFlo is a pump applied self-levelling Alpha Hemihydrate floor screed, manufactured to BS EN 13813 and installed by our own team of trained professionals in strict accordance to BS 8204-7. HydriFlo can be used for (bonded construction) subfloor levelling to create a flat, level and smooth surface. The unique properties of HydriFlo makes the screed ideally suited for placement over thermal and acoustic insulation (floating construction).

The No. 1 choice

HydriFlo has become the number one choice for application over underfloor heating and with good reason. HydriFlo is applied in liquid form, therefore fully encapsulating the underfloor heating pipes, leaving no air pockets. Direct heat transfers into the dense screed resulting in a much more efficient and responsive underfloor heating system. The screed is applied in much reduced thickness (generally 50mm) compared to sand & cement screeds and therefore provides much better insulation or U-values, as thicker floor insulation can be used.

Speedy installation

HydriFlo does not shrink or curl and it can be installed with much fewer joints at great speed. Application up to 1000m² a day is possible.


Contact us for a no-obligation free quotation.

We start with a site visit, advise you on depths regarding insulation and screed, and pre-plan floor coverings. After your screed is installed, we advise you on the aftercare.



HydriFlo is the number one choice for application over underfloor heating and with good reason:

- **Perfect level floors**
- **Improved U-values**
- **Reduced screed thickness**
- **Maximises UFH performance**



1. A smooth and perfectly level screed supplies the ideal base for the floor at the impressive Dromantine Chapel in Newry.

2. The unique properties of HydriFlo make it ideal for placement over thermal and acoustic insulation.

3, 4 & 5. HydriFlo is a pump applied self-levelling floor screed.

6. Factory produced to BS EN 13813.

HydriFlo

Alpha Hemihydrate Self-levelling Floor Screed

Established over 50 years ago, we are the leading manufacturers and suppliers of HydriFlo, Concrete Blocks, Ready Mix Products, Resin Bonded and Resin Bound Aggregates in Ireland.

Please contact us with your requirements for new build, renovation or extension. We are more than happy to assist you with any technical queries and quote you for any of our products and services.

**Tel: +44 (0)28 3026 6421
www.turleybros.com
www.resinbondedireland.com**

Why not come and visit our showroom and experience our products and finishes.



/TurleyBros



The screed literally flows over thermal heating pipes and then self-levels to provide a perfectly flat surface, ready for a variety of floor finishes including tiles and parquet flooring.

